

SPEED POST

F.No. 4-2/2005-FIU-Admn. (Vol.II)
Government of India
Ministry of Finance
Department of Revenue
Financial Intelligence Unit-India

6th Floor, Hotel Samrat,
Kautilya Marg, Chanakyapuri
New Delhi-110021
Dated the 18th April, 2013

NOTICE INVITING QUOTATION

To

All probable vendors.

Subject : **Supply and fixation of one P/F Fire Proof door and frame of door in FIU-India office at 6th Floor Corridor of Hotel Samrat – Quotation regarding.**

Sir,

Sealed Quotations are invited towards supply and fixation of one P/F Fire Proof door including frame in the office of Financial Intelligence Unit-India at 6th Floor Corridor of Hotel Samrat, Kautilya Marg, Chanakyapuri, New Delhi-110021 of size of frame is approx 4ft x 6.5 ft. The detailed specifications as required by the ITDC for fire safety norms for door is given below:

<u>Supply and fixation of one P/F Fire Proof door including frame of approx 4ft x 6.5 ft size.</u>				
S.No.	Description of item	Unit/Qty.	Rate (Rs.)	Amount (Rs)
1.	P/F 55 mm thick asbestos free composite Fire/smoke Check wooden shutter of 120 minutes fire resistance rating confirming to BS:476 part-22&IS:3614 part-II comprising of two 12 mm thick non-combustible boards sandwiching 25 mm tick fire resistance insulation material faced with 3 mm commercial ply on both side with heat activated inducement fire seal strip of size 12x5 mm mounted on grooves of hardwood leaping on three sides except bottom. Finished with two coat of fire retardant paint. 82”x52”	Sqm		
2.	Wooden door frame made of hard wood of section 140x70 mm with heat activated intumescent fire seal strip of section 12x5 mm finished with two coat of fire retardant paint.	Rmt		
3.	P/F fire proof Wired glass of 6 mm thick of 120 minute fire rating in doors complete in all respect as per the direction of engineer in charge	Sqm		

4.	P/F 304 grade SS ball bearing hinges (100x75x2.5) in the door shutter with the frame complete in all respect as per the direction of engineer in charge	Each		
5.	P/F Fire rated door closer in the doors complete in all respect as per the direction of engineer in charge	Each		
6.	P/F 304 grade SS door handle fire raged in the doors complete in all respect as per the direction of engineer in charge.	Each		
7.	Taxes and levies, if any			
	Grand Total			

2. Quotations should be addressed to the Director, FIU-IND, Sealed envelope containing the quotation should be superscribed "Quotation for supply and fixing of one P/F Fire Proof door with frame in FIU-IND" and reach the undersigned on or before 16=00 hours on 02nd May, 2013.

3. You are requested to submit your most competitive rate for the above items as per specification in the format enclosed as Appendix "A". Payment will be calculated on the basis of the actual quantity of each item used and will be released only after successful completion of work and submission of bills.

4. Quotations, complete in all respects should reach this office by 1600 hours on 02nd May 2013

Your faithfully.



(Heera Singh)
Assistant Director (Admn)

Copy to :

- Ms. Sweta, Assistant Programmer, Technical Unit, FIU-India – with a request to kindly upload the notice on our official website.**

APPENDIX-A

Name of the Firm :

Registered/Postal Address :

Telephone No. :

E-mail :

PAN No. :

VAT/TIN No.(if applicable) :

Service Tax Registration (if applicable) :

Do you fulfil all the eligibility conditions :

<u>Supply and fixation of one P/F Fire Proof door including frame of approx 4ft x 6.5 ft size.</u>				
S.No.	Description of item	Unit/Qty.	Rate (Rs.)	Amount (Rs)
1.	P/F 55 mm thick asbestos free composite Fire/smoke Check wooden shutter of 120 minutes fire resistance rating confirming to BS:476 part-22&IS:3614 part-II comprising of two 12 mm thick non-combustible boards sandwiching 25 mm tick fire resistance insulation material faced with 3 mm commercial ply on both side with heat activated inducement fire seal strip of size 12x5 mm mounted on grooves of hardwood leaping on three sides except bottom. Finished with two coat of fire retardant paint. 82"x52"	Sqm		
2.	Wooden door frame made of hard wood of section 140x70 mm with heat activated intumescent fire seal strip of section 12x5 mm finished with two coat of fire retardant paint.	Rmt		
3.	P/F fire proof Wired glass of 6 mm thick of 120 minute fire rating in doors complete in all respect as per the direction of engineer in charge	Sqm		
4.	P/F 304 grade SS ball bearing hinges (100x75x2.5) in the door shutter with the frame complete in all respect as per the direction of engineer in charge	Each		
5.	P/F Fire rated door closer in the doors complete in all respect as per the direction of engineer in charge	Each		
6.	P/F 304 grade SS door handle fire rated in the doors complete in all respect as per the direction of engineer in charge.	Each		
7.	Taxes and levies, if any			
	Grand Total			

Signature with seal